



1S

	2535	1700	1190
	2.43	3.73	5.33
	5585	3745	2620
	7'11"	12'2"	17'5"
790 kg			
1740 lb			

2S

	2455	1610	1110	835
	2.43	3.82	5.42	7.10
	5410	3545	2445	1840
	7'11"	12'6"	17'9"	23'3"
870 kg				
1915 lb				

3S

	2375	1505	1015	750	600
	2.43	3.91	5.51	7.19	8.89
	5235	3315	2235	1650	1320
	7'11"	12'9"	18'0"	23'7"	29'2"
1070 kg					
2355 lb					

4S

	2285	1435	955	690	540	445
	2.43	4.00	5.59	7.27	8.95	10.65
	5035	3160	2105	1520	1190	980
	7'11"	13'1"	18'4"	23'10"	29'4"	34'1"
1135 kg						
2500 lb						

Standard



Optional



MODEL							
	txm	(°)	mm	mm	mm	mm	t
1S	6,34	370	1990	2230	615	4623	6,5
2S	6,15	370	1990	2230	615	4623	6,5
3S	5,88	370	1990	2240	615	4623	6,5
4S	5,74	370	1990	2300	615	4623	6,5

MODEL							
	lb*ft	(°)	in	in	in	in	lb
1S	45870	370	78	88	24	182	14300
2S	44500	370	78	88	24	182	14300
3S	42540	370	78	88	24	182	14300
4S	41530	370	78	90	24	182	14300