



1S

	2835	1950	1380	kg
	2.55	3.82	5.42	m
915 kg	6250	4295	3040	lb
2015 lb	8'4"	12'6"	17'9"	ft

2S

	2725	1835	1265	960	kg
	2.55	3.91	5.51	7.21	m
995 kg	6005	4045	2785	2115	lb
2190 lb	8'4"	12'9"	18'	23'7"	ft

3S

	2645	1740	1180	900	700	kg
	2.55	4.00	5.6	7.30	9	m
1070 kg	5830	3835	2600	1980	1540	lb
2355 lb	8'4"	13'1"	18'4"	23'11"	29'6"	ft

4S

	2545	1640	1110	815	645	520	kg
	2.55	4.09	5.69	7.39	9.09	10.79	m
1135 kg	5610	3615	2445	1795	1420	1145	lb
2500 lb	8'4"	13'5"	18'8"	24'2"	29'9"	35'4"	ft

Standard



Optional



MODEL							
	txm	(°)	mm	mm	mm	mm	t
1S	7,48	380	2095	2215	635	3382 4857	9
2S	7,17	380	2095	2215	635	3382 4857	9
3S	6,96	380	2095	2240	635	3382 4857	9
4S	6,71	380	2095	2300	635	3382 4857	9

MODEL							
	lb*ft	(°)	in	in	in	in	lb
1S	54120	380	82	87	25	133 191	19800
2S	51880	380	82	87	25	133 191	19800
3S	50360	380	82	88	25	133 191	19800
4S	48550	380	82	90	25	133 191	19800